

# Bulldog AJ10 Hitch Lock Fitting Instructions



## TO FIT THE HITCH LOCK:

1. Hold the head of the lock bar, insert the key and turn it a quarter turn anticlockwise , remove the lock bolt.
2. With the stabiliser handle at full height, lift the hitching handle and insert the false ball.
3. With the two slots in the red hitch cover facing forward, place the cover over the handle.
4. With the key inserted in the lock bolt and in the unlocked position, push the lock bolt through the cover assembly hold the head of the lock bolt, turn the key a quarter turn clockwise and remove keys. Return the stabiliser handle to its lower position.

**Note:** For added protection, this hitch lock can be used whilst car and caravan are hitched. Please note, in these circumstances the false ball is not required.

We have taken every care in the design and manufacture of this security device and we believe that it is an effective deterrent. However we cannot guarantee that it will resist the efforts of the most determined thief and as such we do not accept any liability for loss or damage caused by theft, vandalism or other illegal activity against property to which this device is fitted.



**WARNING.** Before unlocking Hitch Lock with keys provided, please remember to support base with hand - i.e: Mind your feet.

### Lock Lubrication.

**IMPORTANT** - To ensure free movement of the lock, spray outside of lock body with WD40 (or equivalent) minimum every four months.

**Key Security. Enter your key number here:**

**IMPORTANT** - Your Bulldog product is supplied with two keys. Make a note of your personal key number in the space provided above and **keep it in a safe place**. Should you lose your keys, replacements can only be obtained from the manufacturer through your dealer.